FAYTECH® 15.6" ARM TOUCH KIOSK \$905D3 BASIC

FT156S905D3BAKCAPOB v1: GL: 3030516852






DISPLAY

| Display Size [inch] | 15.6 |
|---------------------|-----------------|
| Aspect Ratio | 16:9 |
| Resolution | 1920 × 1080 |
| Active Area [mm] | 344.16 × 193.59 |
| Brightness [cd/m²] | 500 |
| Contrast Ratio | 800:1 |
| LED life time [h] | 15000 |
| Viewing Angle [°] | 170 / 170 |
| Display Interface | eDP |

PC/MONITOR SYSTEM (INTERNAL)

| Processor | Amlogic S905D3 |
|--|--------------------------------|
| Chipset | Quad-Core Cortex A-53 |
| Standard Operating System | Android 9 |
| OS Available on Request (additional fee) | Linux Ubuntu 22.4, Debian 12 * |
| RAM Size | 2 GB LPDDR4 |
| EMMC Size | 64 GB eMMC 5.1 |
| GPU | Mali G31 MP2 |
| NPU | 1.2Tops |
| Loudspeaker | 2× 2W |
| Wifi + BT | RTL8821 + Bluetooth 4.0 |
| SD Card Slot | 1 |
| USB 3.0 | 1 |
| USB 2.0 | 1 |
| USB OTG | 1 |
| Ethernet Network (10/100/1000 Mbit/s) | 1 |
| Serial Port RS232 (RX / TX only) | 1 |

SERIAL (RS232) PIN DEFINITION



| 2 | RXD1 | |
|----|------|--|
| 3 | TXD1 | |
| 5 | GND | |
| 10 | GND | |
| 11 | GND | |

TOUCH PANEL

| Touch Type | Projected Capacitive 10-point Multi-touch |
|--------------------------------|---|
| Printing Type | Organic |
| Glass Thickness [mm] | 1.1 |
| Cover Glass Surface Treatement | AG |
| IK Protection | IK07 |
| Printing Color | RAL9004 (Black) |
| Strengthening | Thermally Strengthened |
| Touch Controller | EXC81W84 |
| Touch Interface | USB |
| Touch Resolution RX | 53 |
| Touch Resolution TX | 30 |
| Ontical Bonding | Clear Bond® |

ENVIRONMENTAL CONDITIONS

| Operation Temperature | -10°C to 60°C | |
|-----------------------|---------------|--|
| Storage Temperature | -20°C to 60°C | |
| Humidity Range | 10% to 90% | |

CERTIFICATIONS

| CE Certificate | Yes |
|-----------------|-----|
| FCC Certificate | Yes |

CHASSIS

| Case Design | Glass + Aluminum |
|--------------------------|------------------------|
| IP Protection | IP65 Front / IP40 Back |
| Case Color | RAL9004 (Black) |
| Case Coating | Powder Coating |
| Case Material | Aluminum |
| Case size L × W × H [mm] | 350.0 × 300.0 × 1196.9 |
| Mounting | Stable base |



[&]quot;) faytech Tech Co., Ltd. is not affiliated with Debian. Debian is a registered trademark owned by Software in the Public Interest, Inc. Debian 12 OS does not require additional fee.



ACCESSORIES

| Power Adapter | 100-240V ACDC active switching; 12V DC-Out |
|--------------------------|--|
| Short Instruction manual | Yes |

INTENDED USE/APPLICATION

The device is to be used as touchscreenk display for indoor use as information display, digital signage, way-finding, POS and similar applications.

Direct sunlight might increase the device temperature beyond the allowed storage and operation conditions. Therefore the devices must be protected against direct sunlight. Devices operated or stored outside the specified temperature ranges are not covered by warranty.


POWER


| Power Indicator | Green LED |
|---|-----------|
| Working Power | 12V |
| Power Consumption | 25W |
| Stand-By Consumption [Android / Ubuntu] | <1W / <3W |


WEIGHT & PACKAGING

| Net Weight | 30.0 kg |
|-------------------------------|---|
| Gross Weight | 65.0 kg (incl. Cartonage) |
| Packaging Material | Eco-friendly wooden crate and polyethylene (PE) |
| Packaging Size L × W × H [mm] | 533.4 × 533.4 × 1397.0 |

DIMENSIONS







Tolerance: ± 2 mm

UPDATE NOTES:

| Version: | Changes: |
|----------|---------------|
| v1 | First version |

